

**PATENTS
PENDING**

F-SERIES SPLIT RETROFIT-S

FOR SINGLEWALL FIBERGLASS SUMPS
FRP SPLIT FITTING FOR RETROFITTING FLEXIBLE ENTRY BOOTS

Permanently solve the problem !

FEATURES:

- > No excavation needed
- > No disconnecting pipe
- > For flat or round walls
- > Low profile: less than 2"
- > Angle Adjustability: 0 - 20°
- > Tank-Spec FRP material
- > No metal or rubber parts
- > Warranted for fuel submersion
- > 30 Year Corrosion Warranty
- > Only True FRP Retrofit Fitting
- > PERMANENTLY replaces all types of flexible entry boots



IMAGES COURTESY OF BRAVO INSTALLERS



15A



WWW.SBRAVO.COM
800-AT-BRAVO



FITTING MODELS FOR 0-20° DEGREE ADJUSTABILITY				ROUND AND FLAT WALLS			
Model Number	Wall type	Pipe type and size	Angle Adjustability	O.D.	Length	Adhesive Included	List
F-05-Retrofit-S	Flat/Round	1/2" Conduit / RobRoy	0 - 20° deg.	5"ø	2"	1	\$ 172
F-07-Retrofit-S	Flat/Round	3/4" Conduit / RobRoy	0 - 20° deg.	5"ø	2"	1	172
F-10-Retrofit-S	Flat/Round	1" Conduit / RobRoy	0 - 20° deg.	5"ø	2"	1	172
F-20-Retrofit-S	Flat/Round	2" Fiberglass	0 - 20° deg.	7"ø	2"	2	224
F-30-Retrofit-S	Flat/Round	3" Fiberglass	0 - 20° deg.	7"ø	2"	2	224
F-40-Retrofit-S	Flat/Round	4" Fiberglass	0 - 20° deg.	8"ø	2"	2	224
F-20-Retrofit-S-LCX	Flat/Round	2" Ameron LCX	0 - 20° deg.	7"ø	2"	2	224
F-30-Retrofit-S-LCX	Flat/Round	3" Ameron LCX	0 - 20° deg.	7"ø	2"	2	224
F-40-Retrofit-S-LCX	Flat/Round	4" Ameron LCX	0 - 20° deg.	8"ø	2"	2	224

FITTING MODELS FOR 20-45° DEGREE ADJUSTABILITY				FLAT WALLS ONLY			
Model Number	Wall type	Pipe type and size	Angle Adjustability	O.D.	Length	Adhesive Included	List
F-05-Retrofit-2045-S*	Flat	1/2" Conduit / RobRoy	20 - 45° deg.	7"ø	2"	3	\$ 286
F-07-Retrofit-2045-S*	Flat	3/4" Conduit / RobRoy	20 - 45° deg.	7"ø	2"	3	286
F-10-Retrofit-2045-S*	Flat	1" Conduit / RobRoy	20 - 45° deg.	7"ø	2"	3	286
F-20-Retrofit-2045-S*	Flat	2" Fiberglass	20 - 45° deg.	7"ø	2"	4	338
F-30-Retrofit-2045-S*	Flat	3" Fiberglass	20 - 45° deg.	8"ø	2"	5	390
F-40-Retrofit-2045-S*	Flat	4" Fiberglass	20 - 45° deg.	9"ø	2-1/2"	5	494
F-20-Retrofit-2045-S-LCX*	Flat	2" Fiberglass	20 - 45° deg.	8"ø	2"	4	338
F-30-Retrofit-2045-S-LCX*	Flat	3" Fiberglass	20 - 45° deg.	9"ø	2"	5	390
F-40-Retrofit-2045-S-LCX*	Flat	4" Fiberglass	20 - 45° deg.	11"ø	2-1/2"	5	494

FITTING MODELS FOR 20-45° DEGREE ADJUSTABILITY				ROUND WALLS ONLY			
Model Number	Wall type	Pipe type and size	Angle Adjustability	O.D.	Length	Adhesive Included	List
F-05-Retrofit-2045-S-RND*	Round	1/2" Conduit / RobRoy	20 - 45° deg.	7"ø	2"	3	\$ 328
F-07-Retrofit-2045-S-RND*	Round	3/4" Conduit / RobRoy	20 - 45° deg.	7"ø	2"	3	328
F-10-Retrofit-2045-S-RND*	Round	1" Conduit / RobRoy	20 - 45° deg.	7"ø	2"	3	328
F-20-Retrofit-2045-S-RND*	Round	2" Fiberglass	20 - 45° deg.	7"ø	2"	4	380
F-30-Retrofit-2045-S-RND*	Round	3" Fiberglass	20 - 45° deg.	8"ø	2"	5	411
F-40-Retrofit-2045-S-RND*	Round	4" Fiberglass	20 - 45° deg.	9"ø	2-1/2"	5	546
F-20-Retrofit-2045-S-LCX-RND*	Round	2" Fiberglass	20 - 45° deg.	8"ø	2"	4	380
F-30-Retrofit-2045-S-LCX-RND*	Round	3" Fiberglass	20 - 45° deg.	9"ø	2"	5	411
F-40-Retrofit-2045-S-LCX-RND*	Round	4" Fiberglass	20 - 45° deg.	11"ø	2-1/2"	5	546

* All 20-45° Degree models include an Offset Plate kit

OFFSET PLATES FOR GREATER WALL CONTACT		
Model Number	Description	List
F-2x7-OFFSET-S	2" I.D. x 7" O.D. split FRP offset for Flat Walls	\$ 84
F-2x7-OFFSET-S-RND	2" I.D. x 7" O.D. split FRP offset for Curved Walls	84
F-5x10-OFFSET-S	5" I.D. x 10" O.D. split FRP offset for Flat Walls	109
F-5x10-OFFSET-S-RND	5" I.D. x 10" O.D. split FRP offset for Curved Walls	109

EP100-RF	7oz retrofit epoxy kit. includes tools.	\$ 32
----------	---	-------



High-end materials match UST spec UL1316 to ensure longevity and fuel compatibility

