

# DOUBLEWALL TRANSITION PIPING SUMP 42" OR 48" B409-D-AB SERIES UNISUMP OCTAGONAL FIBERGLASS SUMP WITH CLOSED BOTTOM

**Eight Sided Sump  
Great for 45° & 90°  
Fiberglass Fittings**

42" ø has 15" Panels  
48" ø has 18" Panels

New Reinforced  
fiberglass construction

Flat-Wall  
construction  
for easy  
mounting of  
fittings

Ships with factory  
installed combination  
gauge for continuous  
monitoring

Third Party  
Approved  
AB-2481  
Compliant

B409-D-AB features  
a strong, reinforced  
bottom



Adjustable Electronic  
Monitor Housing  
(Sensor not included)

**B409-D-AB**  
Series Doublewall  
Transition Piping  
Sumps available in  
heights between 3' and  
7' with 32" or 36" top  
hat reducer diameters

**Recommended:  
F-Series DB FRP Fitting**



Custom sizes available!  
**Contact us!**



 **Optional:  
UL Approved  
Sumps**

**OPTIONAL HIGH WATER TABLE DESIGNS AVAILABLE!!**



323/888-4133

S. BRAVO SYSTEMS, INC • 2929 Vail Avenue • Commerce • CA • 90040  
Fax: 323/888-4123 • E-mail: info@sbravo.com • www.sbravo.com