



Full Body Entry Fitting: Omegaflex

NEW CONSTRUCTION FITTING



SPECIFICATIONS:

- Quality fiberglass construction and bonded installation provides an extremely long service life compared to flexible entry fittings
- 30 year corrosion warranty
- Nylon adheres bond to flex pipe

Single Wall - (No clamp required, uses Acme thread)

Part #	Description	EP100 Epoxy Req'd	NY-260
F-10-OFLX-CR3.5	OmegaFlex 1" Doubletrac, threaded pass-through 3.5" centering ring	1	2 oz nylon/injection
F-15-OFLX-CR5	OmegaFlex 1-1/2" Doubletrac, threaded pass-through 4.5" centering ring	2	2 oz nylon/injection
F-20-OFLX-CR5	OmegaFlex 2" Doubletrac, threaded pass-through 5.5" centering ring	2	2 oz nylon/injection

Double Wall - (No clamp required, uses Acme thread)

Part #	Description	EP100 Epoxy Req'd	NY-260	PS-400 Tertiary Boot Seal
F-10-OFLX-D-CR3.5	OmegaFlex 1" Doubletrac, threaded for doublewall, pass-through 3.5" centering ring, adhesives req'd	1	2 oz nylon/injection	30ml
F-15-OFLX-D-CR5	OmegaFlex 1-1/2" Doubletrac, threaded pass-through 4.5" centering ring, adhesives req'd	2	2 oz nylon/injection	30ml
F-20-OFLX-D-CR5	OmegaFlex 1-1/2" doubletrac, threaded for doublewall, pass-through 5.5" centering ring, adhesives req'd	2	2 oz nylon/injection	30ml

Innovative Solutions for Secondary Containment

800-282-7286 | www.sbravo.com