



Double Sided Series Entry Fitting: Double Wall Sumps

RETROFIT FITTING



OVERVIEW:

Used for double-sided repairs to eliminate continuous leak point.

SPECIFICATIONS:

- Split design doesn't require disconnecting pipes
- Repairs both interior and exterior leaks with excavation
- 30 year corrosion warranty
- AB2481 compliant

For Flat Sump Walls

Part #	Description	Epoxy Req'd Qty	Flange Diameter
RF-05-03-F	1/2" conduit, double-sided split for flat doublewall sumps, flat walls	2	7"
RF-07-03-F	3/4" conduit, double-sided split for flat doublewall sumps, flat walls	2	7"
RF-10-03-F	1" conduit, double-sided split for flat doublewall sumps	2	7"
RF-20-03-F	2" FRP double-sided split for flat doublewall sumps	2	9"
RF-30-03-F	3" FRP double-sided split for flat doublewall sumps	4	9"
RF-40-03-F	4" FRP double-sided split for flat doublewall sumps	4	9"
RF-20L-03-F	2" LCX FRP double-sided split for flat doublewall sumps	4	9"
RF-30L-03-F	3" LCX double-sided split for flat doublewall sumps	4	9"

Innovative Solutions for Secondary Containment

800-282-7286 | www.sbravo.com



Double Sided Series Entry Fitting: Double Wall Sumps

RETROFIT FITTING

For Round Sump Walls

Part #	Description	Epoxy Req'd Qty	Flange Diameter
RF-05-03-R	1/2" conduit, double-sided split for round doublewall sumps	2	7"
RF-07-03-R	3/4" conduit, double-sided split for round doublewall sumps	2	7"
RF-10-03-R	1" conduit, double-sided split for round doublewall sumps	2	7"
RF-20-03-R	2" FRP double-sided split for round doublewall sumps	2	9"
RF-30-03-R	3" FRP double-sided split for round doublewall sumps	4	9"
RF-40-03-R	4" FRP double-sided split for round doublewall sumps	4	9"
RF-20L-03-R	2" LCX FRP double-sided split for round doublewall sumps	4	9"
RF-30L-03-R	3" LCX double-sided split for round doublewall sumps	4	9"