



Full Body Entry Fitting: Round Sump Walls

NEW CONSTRUCTION FITTING



SPECIFICATIONS:

- Quality fiberglass construction and bonded installation provides an extremely long service life compared to flexible entry fittings
- 30 year corrosion warranty
- Dual integrated test ports that can be used for testing, drainage to a sensor, or VPH constant monitoring
- Available for single or double wall sumps

OVERVIEW:

Termination entry fitting which terminates secondary pipe at the exterior of the containment sump.

Part #	Description	EP100 Epoxy Req'd	Hole Saw Size
F-07S-0-R	3/4" galvanized conduit for round walls, full-body with dual injection ports for round, clamp req'd	2	2 3/4"
F-07RS-0-R	3/4" PVC coated conduit, full-body with dual injection ports for round walls, clamp req'd	2	2 3/4"
F-07S-0-DR	3/4" galvanized conduit, doublewall, full-body, dual injection ports and tertiary boot seal, round wall, FRP, clamps req'd	2	2 3/4"
F-07RS-0-DR	3/4" PVC coated conduit, doublewall, full-body, dual injection ports and tertiary boot seal, round wall, FRP, clamps req'd	2	2 3/4"
F-10S-0-R	1" PVC coated conduit, full-body with dual injection ports, clamps req'd	2	2 3/4"
F-10S-0-DR	1" galvanized conduit, DW full-body, dual injection ports & tertiary boot seal, round wall FRP, clamp req'd	2	2 3/4"
F-10RS-0-R	1" PVC coated conduit, full-body with dual injection ports for round walls, clamp req'd	2	2 3/4"
F-10S-0-DR	1" galvanized conduit, DW full-body, dual injection ports & tertiary boot seal, round wall FRP, clamp req'd	2	2 3/4"
F-10RS-0-DR	1" PVC coated conduit, doublewall full-body with dual injection ports and tertiary boot seal, Round walls, clamp req'd	2	2 3/4"
F-07-GR-R	3/4" brass grounding rod for round walls, full-body with brass conductor and clamps	2	2 3/4"
F-32S-T-R	3x2" FRP, full-body taper by slip; dual test ports and single injection port for round walls	2	4 1/2"
F-43S-T-R	4x3" FRP, full-body taper by slip; dual test ports and single injection port for round walls, clamp req'd	3	5 1/2"
F-64S-T-R	6x4" FRP, full-body taper by slip; dual test ports and single injection port for round walls, clamp req'd	3	8"
F-32A-T-R	3x2" FRP, adjustable full-body taper by slip; dual test ports and single injection port for round walls. clamp req'd	3	4 1/2"
F-43A-T-R	4x3" FRP, adjustable full-body taper by slip; dual test ports and single injection port for round walls, clamp req'd	3	5 1/2"

Parts and Accessories	
T-FS-C10	One 3 bolt in-line compression clamp for F-Series conduit fittings
T-FS-C40	One tripod compression for full body 2", 3" and 4" product
EP100	Bravo Epoxy (6oz Epoxy 1oz Catalyst)

Innovative Solutions for Secondary Containment

800-282-7286 | www.sbravo.com