



Full Body Entry Fitting: Flat Sump Walls

NEW CONSTRUCTION FITTING



OVERVIEW:

Termination entry fitting which terminates secondary pipe at the exterior of the containment sump.

SPECIFICATIONS:

- Quality fiberglass construction and bonded installation provides an extremely long service life compared to flexible entry fittings
- 30 year corrosion warranty
- Dual integrated test ports that can be used for testing, drainage to a sensor, or VPH constant monitoring
- Available for single or double wall sumps

Parts and Accessories	
T-FS-C40	One tripod compression clamp for full body 2", 3" & 4" product fittings
PS-400	Polysulfide adhesive 400ml (12 oz.) dual cartridge with 3 stator mixing tips required man-gun. (1) can do (10) fittings
T-MG400	Manual caulk gun for PS-400
EP100	Bravo Epoxy (6oz Epoxy 1oz Catalyst)

Innovative Solutions for Secondary Containment

800-282-7286 | www.sbravo.com



Full Body: Flat Sump Walls

NEW CONSTRUCTION FITTING

F Series Full-Body Flat Sump Wall

Part #	Description	EP100 Epoxy Req'd	Hole Saw Size
F-07S-0-F	3/4" galvanized conduit, threaded full-body with dual injection ports flat walls.	2	2 3/4"
F-07RS-0-F	3/4" PVC coated conduit, threaded full-body with dual injection ports for flat walls.	2	2 3/4"
F-07S-0-DF	3/4" galvanized conduit, threaded doublewall full-body with dual injection ports flat walls.	2	2 3/4"
F-07RS-0-DF	3/4" PVC coated conduit, threaded full-body with dual injection ports.	2	2 3/4"
F-10S-0-F	1" galvanized conduit, threaded full-body with dual injection ports.	2	2 3/4"
F-10RS-0-F	1" PVC coated conduit, threaded full-body with dual injection ports.	2	2 3/4"
F-10S-0-DF	1" galvanized conduit, threaded doublewall full-body fitting, dual inspection ports and tertiary boot seal, flat wall.	2	2 3/4"
F-10RS-0-DF	1" PVC conduit, threaded doublewall full-body fitting, dual inspection ports and tertiary boot seal, flat wall.	2	2 3/4"
F-07-GR	3/4" brass grounding rod, full-body with brass conductor and clamps	2	2 3/4"
F-32S-T-F	3x2" FRP, threaded full-body taper by slip; dual test ports and single injection port, flat walls.	2	4 1/2"
F-32SL-T-F	2" LCX, threaded full-body taper by slip; dual test ports and single injection port, with o-rings, flat walls. Includes 4" x 2" LCX reducer loose.	3	4 1/2"
F-32C-T-F	3X2" Threaded Full Body Termination, 2" Coupling, Dual test ports, tapered primary and secondary connection, Flat walls.	2	4 1/2"
F-32CL-T-F	3X2" Threaded Full Body Termination, 2" Coupling, Dual test ports, tapered primary connection, Flat Wall. Includes 4" x 2" LCX reducer loose.	3	4 1/2"
F-43S-T-F	4x3" FRP, full-body taper by slip; dual test ports and single injection port, flat walls. Clamp Req'd.	2	5 1/2"
F-64S-T-F	6x4" FRP, full-body taper by slip; dual test ports and single injection port, flat walls. Clamp Included.	3	8"
F-32A-T-F	3x2" FRP, adjustable full-body taper by slip; dual test ports and single injection port. Clamp Req'd.	3	4 1/2"
F-43A-T-F	4x3" FRP, adjustable full-body taper by slip; dual test ports and single injection port, flat walls. Clamp Req'd.	3	5 1/2"

UF Series, Universal Fitting Full-Body

Pipe Type	Part #	Description	EP100RF Req'd
3x2 FRP and 2" LCX	F-32U-T-F	3x2" FRP, 2" LCX, Threaded, universal full-body termination for size-over-size and LCX pipe; dual test ports, flat walls.	2
4X3" FRP and 3" LCX	F-43U-T-F	4x3" FRP, 3" LCX, Threaded, universal full-body termination for size-over-size and LCX pipe; dual test ports, flat walls.	2